



A05 PRIMER

Adhesion promoter for plastic materials

A) DESCRIPTION AND FIELDS OF APPLICATION:

One-component product for all plastic parts of cars. Can be used on every type of paints and on every product used for repairs of plastic materials.

B) TECHNICAL DATA:

Composition	Solution of synthetic resins with cementing action
Specific weight	0,85± 0,02
Available colours	Colourless
Safety data	See safety data sheet

C) PROCESSING :

Apply a thin layer of A05 Primer on the surface to be repaired or repainted.
Can be overcoated after 5-10 minutes at 20°C.

D) CAUTIONS:

- * Wash the surface with V12 water Cleaner, before application of A05 Primer
- * Do not apply in too thick coats
- * Drying time may change depending on temperature and damp.

Technical indications and advices are based on our own experiences. We assure the perfect quality of products. However, being the utilization out of our control, we assume no responsibility on the results obtained

INDUSTRIA CHIMICA REGGIANA - I.C.R. S.p.A

42100 Reggio Emilia - Via M. Gasparini, 7 - Tel. +39 0522 517803 - Fax +39 0522 514384 - e-mail: icr@icrsprint.it - www.icrsprint.it

Uff. Comm.le Italia: 42100 **Reggio Emilia** - Via Neviani, 5 - Tel. +39 0522 517803 - Fax +39 0522 231819

International Department: 42100 **Reggio Emilia** - Via Neviani, 5 - Tel. +39 0522 513738 - Fax +39 0522 512446

Stabilimento: 42025 **Cavriago** - Via Nizzola, 5 - Tel. +39 0522 371818 - Fax +39 0522 575110

Stabilimento: 06074 **Perugia** - Via Trasimeno Ovest, 159/Z/13 - Tel. +39 075 518611 - Fax +39 075 5186125

CAPITALE SOC. € 557.820,00 - R.E.A. N. 82109 M. R.E. 000534 - Reg. Imprese, COD. FISC. e PART. IVA 00140910357